



FS-1100

Small Workgroup Printer

WORK HARD.
PRINT SMART.™



- ▶ Fast 30 Page per Minute Black & White Printer
- ▶ Standard 1200 dpi Print Resolution for Crisp Output
- ▶ Standard 32MB Memory
- ▶ High Speed 2.0 Connection
- ▶ Optional Network Interface Card Available
- ▶ ECOSYS® Printers use Long Life Consumables, Reducing Costs
- ▶ Low Total Cost of Ownership

FS-1100 SPECIFICATIONS

PRINTER SPECIFICATIONS

BASIC SPECIFICATIONS:

| | |
|--------------------------|--|
| Configuration: | Small Workgroup Black & White Printer with 250 Sheet Drawer, Single Sheet Multi-Purpose Tray and Optional Network Card |
| Resolution: | Fine 1200 mode (1,200 x 1,200 dpi), Fast 1200 mode (1,800 x 600 dpi), 600 x 600 dpi, 300 x 300 dpi |
| Printer Memory: | Standard 32MB, upgradable to 544MB via 100 pin DDR DIMMs; Standard CF Card Slot (Type 1) |
| Electrical Requirements: | 120V, 60Hz, 7.5A |
| Dimensions: | 14.8"W x 15.5"D x 9.8"H |
| Weight: | 22.1 lbs |
| Max Duty Cycle: | 20,000 Pages Per Month |

CONTROLLER SPECIFICATIONS:

| | |
|-----------------------------|---|
| Controller: | PowerPC405F5/360MHz |
| Supported PDL / Emulations: | PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), Diablo 630, IBM ProPrinter X24E, Epson LQ850, Line Printer |
| Fonts: | 80 Outline Fonts for PCL6/KPDL3, 1 Bitmap Font |
| Operating System Support: | Windows® 2000/XP/Vista; Mac OS 10.x; Linux |
| Connectivity / Interface: | Hi-Speed USB 2.0 |
| KUIO LV Enhancement Slot: | Optional Network Interface (IB-23) |
| Network Support: | Please refer to IB-23 Section |
| Drivers: | KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers, Generic Driver for Windows Legacy |
| Utilities: | KM-NET Viewer, IC-Link, Status Monitor, PRESCRIBE Utilities |

PAPER SUPPLY:

| | |
|-------------------------|--|
| Standard Paper Sources: | 250 Sheet Drawer, Single Sheet MPT |
| Drawer Paper Size: | LTR, LGL, Oficio2, A4, A5, B5, A6, Folio |
| MPT Paper Size: | LTR, LGL, Oficio2, A4, A5, B5, A6, Folio Custom (2.8" x 5.8" - 8.5" x 14.0") |
| Std/Max Paper Capacity: | 251 Sheets/501 Sheets |
| Paper Weight: | 16 - 32 lb Bond via Paper Drawer, 16 lb Bond - 110 lb Index via MPT |
| Input Materials: | Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes |

OUTPUT SPEEDS:

| | |
|-------------------|--|
| Warm-Up Time: | Less than 15 Seconds (From Sleep Mode) |
| First Print Out: | Less than 6 Seconds (EcoFuser Off) |
| Pages Per Minute: | 30 Letter, 24 Legal |

PAPER HANDLING OPTIONS & ACCESSORIES:

PAPER DRAWER: PF-100

| | |
|----------------------|--|
| Paper Capacity: | 250 Sheets |
| Maximum Drawers: | 1 |
| Paper Weight: | 16 - 32 lb Bond |
| Paper Sizes: | LTR, LGL, Oficio2, A4, A5, B5, A6, Folio |
| Dimensions / Weight: | 14.7"W x 15.4"D x 3.9"H / 7.7lbs or less |

NETWORK INTERFACE CARD: IB-23

| | |
|---------------------|---|
| Interface: | KUIO LV |
| Supported Protocol: | TCP/IP, IPX/SPX, AppleTalk, NetBEUI |
| Windows® Support: | Windows® 2000/XP/2003/Vista |
| Novell® Support: | Novell Netware® 5.x/6.x |
| Mac OS Support: | OS 9.x/10.x |
| UNIX OS Support: | Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR) |
| Network Protocols: | TCP/IP, IPX/SPX, AppleTalk, NetBEUI, NetBIOS over TCP/IP |
| Security Protocols: | IP Filtering, SSL/TLS (HTTPS), SNMP V2c/V3, IPv6, IEEE802.1x (EAP TLS/PEAP) |
| IPv6 Protocols: | HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMPv6 |
| IPv4 Protocols: | HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMP, SMTP, POP3, SNMP, DNS, WINS, NetBIOS over TCP/IP, SNMP v1/v2c/v3, ThinPrint Compatible, Apple Bonjour Compatible |
| Utility: | KMnet Admin |

ADDITIONAL MEMORY:

| | |
|-------------------|--|
| Available Memory: | 64MB, 128MB, 256MB and 512MB DDR DIMMS |
|-------------------|--|

CONSUMABLES:

| | |
|---------------|---|
| Toner TK-142: | 4,000 pages @ 5% Coverage |
| | Ships with 2,000 pages @ 5% Coverage, ISO 19752 Certified |

Kyocera Mita America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted – and reducing landfill waste.

Kyocera's ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today. Visit our TCO Tracker at www.kyoceramita.com and start saving.



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks and trade names are the property of their respective owners. Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA ©2008 Kyocera Mita America, Inc. IC#855D400126



www.kyoceramita.com